



Uniqe characteristics

Backflow protection unit type EB



## MORA INXX II shower system wall

Sleek, discreet and exceptionally good-looking, the INXX II sets new standards for integrated shower systems. With no visible screws, it sits almost seamlessly on the wall for a clean aesthetic. Mora's leading technology and quality ensure a showering experience beyond compare.

**Article number: 275000.60 Flow 3 bar: 7.4 l/m** 

**Description:** Polished brass PVD

- · Note! Approved in selected markets, Sweden, Norway and Finland
- · Thermostatic mixer with reversible headwork
- · Safety stop at 38°C
- · Ceramic headwork
- · Handle in metal
- Approved non-return valves, EN-Standard EN1717
- · Safety box in stainless steel
- Chrome-plated hose 1500 mm
- Shower head Ø300 mm
- Hand shower Ø90 mm
- · With Easy-Clean anti-limescale system
- Build-in depth (min. 75 mm max. 105 mm)

## Consist of following article number:

- 275030 concealed thermostatic mixer
- 275040 safety box for thermostatic mixer
- 275060.60 cover plate and handle for temperature and flow
- 275400.60 shower pipe 400 mm for wall mounted
- 275415.60 hand shower holder with water outlet
- 209575.60 hand shower Ø90 mm
- 130348.60 shower head Ø300 mm
- S600198.60 shower hose 1500 mm